

Key: Mogul
Door: Swinging
Security Level: Medium/Maximum

120MC HALF-CYCLE DEADLATCH

Description

Series 120MC Deadlatches are pin tumbler, motor-operated locks utilizing a two-position motor cam.

Specify keying as follows:

- 121 Keyed case side
- 122 Keyed cover side
- 126 Keyed both sides

Applications

Series 120MC Deadlatches are suitable for use in medium or maximum security situations to lock cell, corridor or entrance doors. Especially appropriate for areas requiring the latchbolt to remain retracted until it is selected to lock again.

Like all Series 120 locks, the jamb-mounted 120MC Deadlatch is designed for use as part of an electrical system with remote operation and monitoring.

Operations

Standard (1): Unlocks when the motor is energized by either a two or three position, maintained contact switch, or a three position momentary contact switch. Once unlocked, the latchbolt remains retracted until it is selected to lock. Opening and closing the door has no effect on the lock when selected to unlock. The latchbolt extends only when the door is opened and the motor is selected to lock. If the door is closed, it must be opened to extend the latchbolt. Two additional variations on this feature are offered:

Without latchback (1a): Once unlocked, the latchbolt is held retracted only as long as the motor remains in the unlocked position. A maintained-contact switch may be used to keep the latchbolt retracted for an extended period of time.

Relock (1b) 09: Once unlocked, the latchbolt is held retracted until the door is opened. It then extends automatically. This operation requires an additional control wire, and may be cancelled by adding an additional control switch. A momentary-contact switch is used for unlocking, and the auxiliary switch is used for relocking. When the door is opened, the auxiliary switch repositions the motor to a locked position so that the lock will deadlatch on closure.

Knob release(2): 120MC Deadlatches may be specified with knob release on one side, where the knob is always active. Knob may be mounted on the case side, or the cover side.

Key holdback (3): When unlocked by key, the deadlatch remains retracted until relocked by turning the key in the opposite direction. Available one side only.

Note: Key cylinders for locks with key holdback feature must be installed at the factory.

Testing

120MC Series Deadlatches and Maxi-Mogul® Key Cylinders have been tested to 1,000,000 operations.

Standards Compliance

All Series 120MC locks are UL Listed as Burglary-Resistant Mechanisms.

Maxi-Mogul® Key Cylinders meet UL437 requirements.

Standard Features

- **Motor voltage** – 120 VAC
- **Superior durability** – Working parts of stainless steel afford greater strength and corrosion resistance.
- **Standard lock size** – All models use the same size case, cover and mounting holes for simplified installation and frame preparation.



- **External two-piece plug connector** – All models install without cover removal. Simple plug-in connection to field wiring.
- **External mounting holes** – Easy installation, and eliminate the need for cover removal.
- **Standard lock** – Mounts behind frame and does not require a faceplate.
- **1" throw latchbolt** – Offers greater security. Each bolt is hardened to resist sawing. When latchbolt is engaged in strike, bevel is concealed to prevent picking.
- **Mechanical unlocking by key** – Specify Folger Adam Mogul cylinders, Maxi-Mogul® high security cylinders or other Mogul cylinders.
- **Investment-cast stainless steel strike** – Furnished with four tamper-resistant screws.
- **Fractional HP Motor** – Permanently lubricated for smooth quiet operation with thermal overload protection and a brake for accurate locking position.
- **Finish** – Zinc plated case and cover.

For more information, please call 210.533.1231.



Key: Mogul
Door: Swinging
Security Level: Medium/Maximum

120MC HALF-CYCLE DEADLATCH

Optional Features

- **Faceplate** – US32D finish.
- **Indication/auxiliary switches** – An indication switch monitors the deadlock lever indicating a deadlocked latchbolt. The auxiliary switch monitors the latchbolt for extended or retracted position.
- **Local electric key (LEK)** – A unique function which uses two types of keys for applications where inmates carry their own keys, but supervision is necessary. One key turns in one direction only and operates the lock electrically. The supervisory key turns in both directions to operate the lock electrically or mechanically. The electric operation may be cancelled from a central console or control point at any time via a three-position switch. The Maxi-Mogul® key cylinder is uniquely suited for this high frequency operation, shown by cycle test of 1,000,000 operations. LEK not available on any 120MC-3 Series Locks.


- **Key Cylinder Extension** – When the lock is keyed on the stop side of the jamb, an extension eliminates the need for a special, recessed frame pocket.
- **Optional motor voltage** – 24 VAC or 24 VDC.

Dimensional Data

Note: Dimensions are for information and planning purposes only, and should not be used as templates.

The chart at right shows applicability of above options to all 120MC Models.

For complete details, see How to Specify in this section.



Specifications

- **Case and cover** – 10 gauge steel.
- **Latchbolt** – Investment-cast stainless steel, hardened, 1" throw.
- **Deadlock lever** – Stainless steel, adjustable for door gap variations.
- **Bolt opening** – Does not allow access to mechanism.
- **Roller bolt** – Investment-cast stainless steel with stainless steel roller.
- **Operating lever** – Stainless steel to operate with motor.

- **Strike** – Investment-cast stainless steel, attached with screws in two directions.
- **Motor** – 120 VAC continuous duty, 24 VAC or 24 VDC optional, synchronous-type gearmotor.
- **Springs** – Stainless Steel.

Electrical Characteristics

- **AC motors** – Synchronous-type gearmotor with brake.
Ratings:
120 VAC: 60 Hz, 1.3 amps at full load.
- **DC motors** – Permanent-magnet gearmotor.
Ratings: 24 VDC, 2.2 amps at full load.
- **Switches** – SPDT, UL Listed, 15 amps @ 125 or 250 VAC.

MODEL NO.	OPERATION	LATCHBACK		RELOCK SWITCH	INDICATION SWITCHES		LEK AVAILABLE
		WITH	W/O		DEADLATCH	AUX	
120MC-1-01	Standard (1)	X			X		Yes
120MC-1-04	Standard (1a)		X		X		Yes
120MC-1-09	Standard (1b)		X	X	X		Yes
120MC-2-01	Knob Release (2)	X			X		Yes
120MC-2-04	Knob Release (2)		X		X		Yes
120MC-2-09	Knob Release (2)		X	X	X		Yes
120MC-3-01	Key Holdback (3)	X			X		No
120MC-3-04	Key Holdback (3)		X		X		No
120MC-3-09	Key Holdback (3)		X	X	X		No





HOW TO SPECIFY 120 SERIES LOCKS

1 2 3 4 5 6 7 8 9
126 E - 1 - 01 x M0-US26D x LHRB x 120 VAC x LEK-2 x E3

1
Keying Location

121
Case Side

122
Cover Side

126
Both Sides

2
Basic Models Deadlatches

E
Solenoid

M
Full-Rotation Motor

MC
Two-Position Motor

Deadbolts

ED
Solenoid

RUP
Solenoid (Roll-Up Door)

3
Operation Series

1
Standard

2
Knob Release

3
Holdback by Key (one side only)

4
Switch Functions

01
Deadlock Indication Switch With Latchback

04
Deadlock Indication Switch No Latchback

07
Electric Holdback

5
Key Cylinder and Finish

Folger Adam Mogul

M
Prep. Only

M0-US26D
110 Mogul Cylinder with US26D Finish

M1-US26D
190-1 Maxi-Mogul® Key Cylinder with US26D Finish

190-A
ASSA Mogul Key Cylinder with US26D Finish

190M
Medeco Mogul Key Cylinder with US4 Finish

Available Key Cylinder Finishes:

US26D (standard)
US26D

6
Lock Handing* Deadlatches

LHRB
Left Hand Reverse Bevel

RHRB
Right Hand Reverse Bevel

Deadbolts

LH
Left Hand

RH
Right Hand

*For application handing see the handing chart on the following page.

7
Operating Voltage

Solenoid
120 VAC
230 VAC

Motor
120 VAC
24 VDC

8
LEK Feature

LEK-1
Case Side

LEK-2
Cover Side

LEK-6
Both Sides

9
Key Cylinder Extension

E3
3" Long

E4
4" Long

E5
5" Long

For more information, please call 210.533.1231.










HOW TO SPECIFY 120 SERIES LOCKS

Specify circled swing number when ordering.

<p>126 LOCK LOCK COVER HINGE SIDE EXTENDED MOUNTING COVER STOP SIDE KEYED BOTH SIDES POCKET COVER PLATE HINGE SIDE</p>	<p>25 DEADBOLT- LATCHBOLT- LH LHRB RH RHRB 26</p>	<p>26 DEADBOLT- LATCHBOLT- RH RHRB LH LHRB 25</p>
<p>126 LOCK EXTENDED MOUNTING COVER HINGE SIDE KEYED BOTH SIDES POCKET COVER PLATE STOP SIDE</p>	<p>41 DEADBOLT- LATCHBOLT- LH LHRB RH RHRB 42</p>	<p>42 DEADBOLT- LATCHBOLT- RH RHRB LH LHRB 41</p>
<p>122 LOCK LOCK COVER HINGE SIDE EXTENDED MOUNTING COVER STOP SIDE KEYED HINGE SIDE POCKET COVER PLATE HINGE SIDE</p>	<p>27 DEADBOLT- LATCHBOLT- LH LHRB RH RHRB 28</p>	<p>28 DEADBOLT- LATCHBOLT- RH RHRB LH LHRB 27</p>
<p>122 LOCK EXTENDED MOUNTING COVER HINGE SIDE KEYED HINGE SIDE POCKET COVER PLATE STOP SIDE</p>	<p>43 DEADBOLT- LATCHBOLT- LH LHRB RH RHRB 44</p>	<p>44 DEADBOLT- LATCHBOLT- RH RHRB LH LHRB 43</p>
<p>121 LOCK LOCK COVER HINGE SIDE EXTENDED MOUNTING COVER STOP SIDE KEYED STOP SIDE POCKET COVER PLATE HINGE SIDE</p>	<p>29 DEADBOLT- LATCHBOLT- LH LHRB RH RHRB 30</p>	<p>30 DEADBOLT- LATCHBOLT- RH RHRB LH LHRB 29</p>
<p>121 LOCK EXTENDED MOUNTING COVER HINGE SIDE KEYED STOP SIDE POCKET COVER PLATE STOP SIDE</p>	<p>45 DEADBOLT- LATCHBOLT- LH LHRB RH RHRB 46</p>	<p>46 DEADBOLT- LATCHBOLT- RH RHRB LH LHRB 45</p>

LEGEND

-  = INDICATES KEYED SIDE (OR SIDES)
-  = SYMBOLIZES LOCK POCKET COVER PLATE
-  = SYMBOLIZES LATCH BOLT (DEADBOLT NOT SHOWN FOR CLARITY)
-  = SYMBOLIZES LOCK CASE
DOUBLE LINE SYMBOLIZES FRONT COVER
-  = THICK LINE SYMBOLIZES REINFORCED STEEL FOR LOCK AND POCKET COVER PLATE MOUNTING

