



## 1030AD Deadlock



## Mechanical Locks

For More information please call 210-123-4567



# Mechanical Locks

## 1030AD Deadlock



### STANDARD FEATURES

- Manual deadlocking
- Six heavy-duty tumblers
- Mounting fasteners

### APPLICATION

High security sliding doors at holding cells, low traffic corridors and cutoff doors. Sliding door normally requires a Model 1300 Track Set.

### FUNCTION

Key activated locking and unlocking of hook bolt. Does not snaplock upon closing.

### OPTIONAL FEATURES

**KNOB FUNCTION** - Knob will retract hook bolt. Knob on one side only. No key required. Specify "1030ADK." Knob finish US26D.

**HOLLOW METAL MOUNTING** - Used for hollow metal door application. Specify "HM."


**GRATING DOOR MOUNTING** -  
Used for grating door application. Specify "G."

1030AD-1: KEYED ONE SIDE  
1030AD-2: KEYED BOTH SIDES



For More information please call 210-123-4567

## 1030AD Deadlock




LOCK: \_\_\_\_\_  
MOUNTING: \_\_\_\_\_

NH RH \_\_\_\_\_ NH LH \_\_\_\_\_

KEYED: BOTH SIDES  
COVER PLATE: DOOR SIDE

(25) \_\_\_\_\_ (26)



## TECHNICAL DATA

|                             |                                  |
|-----------------------------|----------------------------------|
| <b>Standard Finish</b>      | Galvanized                       |
| <b>Cover</b>                | Cold-rolled Steel                |
| <b>Case</b>                 | Ductile iron                     |
| <b>Hookbolt</b>             | Cold-rolled, case-hardened steel |
| <b>Paracentric Cylinder</b> | Silicon bronze/ copper alloy     |
| <b>Tumblers</b>             | 6 tumblers per lock              |
| <b>Lock Size</b>            | 4.4" L x 3.15" H x 1.35" TK      |
| <b>Lock Weight</b>          | 3 lbs                            |
| <b>Lockbolt Size</b>        | 1-1/2" H x 3/4" TK               |
| <b>Latchbolt</b>            | 5/8" extended 1/2" travel        |

