

<b>GENERAL LUBRICATION RULES</b>	<b>The only safe place for oil is in a sealed gearbox. Don't mix lubricants-graphite with oil-based lubricant creates a paste that gums up locks. If this happens, flush and reapply lubricant. Less is more! If you suspect over-lubrication, flush and reapply lubricant.</b>
<b>Recommended Lubricant</b>	<b>Application</b>
<b>FOLGER ADAM® LOCK LUBRICATION</b>	
Tufoil® Lightning Grease	Wearing surfaces for stainless steel castings and stainless stamped parts. Pivot points with larger springs. Examples: 30, 51, 60, 70, 110, 120, 125 and NS400 locks.
Tri-Flow® Industrial Lubricant with PTFE or equal	Use for all Folger Adam mogul cylinders including Maxi-Mogul® and 110 series mogul. Apply a thin coat to edge of lever tumblers, springs. For all paracentric locks. Apply a thin coat to 5-pin mogul pin tumblers and between cylinder plug and body. Examples: NS400 solenoid, 120, 50, NS400 and 9300 locks. Also used for hinges.
Tufoil® Lubit-8®	Pivot pints for stainless steel parts with light springs. Edges of solenoid plungers with stainless guides. Examples: 51 lock, 120 series, including 120E Retro, 800 series, NS400 series and 9300 solenoid locks.
<b>FOLGER ADAM® LUBRICATION FOR SLIDING DEVICES</b>	
SLIP Plate® #3 - use with spray gun Slip-Plate #1 - aerosol can	Sprayed thin on steel mechanism plates and rack bars. Protects against rust and acts as a lubricant when dry. Dry film does not attract dust and grit.
<b>SOUTHERN STEEL® LOCK LUBRICATION</b>	
Tufoil® Lightning Grease	Apply a thin coat between steel-to-steel sliding surfaces, and brass cylinder-to-case or cylinder-to-bolts in locks. Also used on galvanized steel parts to steel cases. Use on 10500 and 10600 locks.
Tri-Flow® Industrial Lubricant with PTFE or equal	Apply a thin coat to edge of lever tumblers, springs. For all paracentric locks. Apply a thin coat to SS 5-pin mogul pin tumblers and between cylinder plug and body. Examples: 1010 paracentric locks, 1017A/AM, 1050 locks, 1030 series locks, 1051 series locks, 1070 locks, 1080 locks, 10370, 10380 cremone bolt sets. Also for hinges.
Spray Petroleum Lubricant #807718. Purchase spray from any authorized ASSA distributor.	Apply a thin coat to 6-pin mogul pin tumblers and between cylinder and plug and body for all 6-pin mogul locks. Example: 1010AMP. Do not use graphite or silicone lubricants!
Super-STA #2 Multipurpose Lithium Grease (Conoco)	Apply to wearing surfaces for stainless steel castings and stainless stamped parts. Pivot points with larger springs; pivot points for stainless steel parts with light springs. Examples: 1010AMP, 1058MD, 10120 series, 10300 series, 1017AM/AL, 1030 series locks, 1051 series, 1070 locks, 1080ASD, 10501, 10370 and 10380.
<b>SOUTHERN STEEL® LUBRICATION FOR SLIDING DEVICES</b>	
SLIP Plate® #3 - use with spray gun Slip-Plate #1 - aerosol can	Thin coat applied to gang release bar and drive rack assembly. Protects from rust and corrosion. Dry film does not attract dust and grit.
<b>Cleaners</b>	<b>Applications</b>
Simple Green All-Purpose Cleaner	For degreasing locking mechanisms, in all cases, especially plastics, a small area should be tested prior to use to ensure no damage to the components. All of these cleaners are CFC-Free.
CRC Citrus Degreaser #14170	