



1051P Pneumatically Operated Deadlatch



Pneumatic Locks



For More information please call 210-533-1231

Pneumatic Locks

1051P Pneumatically Operated Deadlatch



APPLICATION

For maximum security swinging doors that are to be unlocked from a remote location. Jamb mounted. Door position indicator switch, door closer and heavy duty door pull are recommended.

FUNCTION

ELECTRIC - Remote switch activates a pneumatic cylinder which retracts the latchbolt. Latchbolt remains retracted until door is opened approximately 2", then it releases, automatically latches and deadlocks when the door is closed.

MECHANICAL - Latchbolt is retracted by a paracentric key at the door and remains retracted until door is opened approximately 2", then it releases, automatically latches and deadlocks when the door is closed.

Automatic deadlatch feature is suspended when paracentric key is rotated to mechanical key hold-back position. Normal function is resumed when key is returned to deadlocked position.

STANDARD FEATURES

- Deadlock indication switch
- Mechanical latchback
- Six tumbler lock
- Plug connector
- Solenoid valve
- Fail secure
- Mounting fasteners
- Mechanical key holdback
- Adjustable roller bolt

OPTIONAL FEATURES

NO LATCHBACK - Latchbolt remains retracted as long as control switch is activated. Latchbolt extends when power is removed. Specify "NL."

EMERGENCY EXIT DOOR HOLDBACK - Deadbol retracted by solenoid or by key, extended by key only (no snaplatch feature). When deadbolt is extended, lock is deadlocked. Specify "EED."

UL listing not available with this function.


EMERGENCY EXIT RELEASE From remote location latchbolt can be retracted and held retracted until released from remote station. Requires a second pneumatic tube to the lock and an emergency reserve air system. Specify "EER."

UL listing not available with this function.







Pneumatic Locks

1051P Pneumatically Operated Deadlatch



Swing Chart: Specify circled swing number when ordering.



* Indicates lock mounting/access plate side.

TECHNICAL DATA

Standard Finish	Galvanized
Cover	3/16" steel plate
Case	3/16" steel plate
Latchbolt	2" H x 3/4" TK Cold-rolled steel
Deadlock Actuator	Stainless steel
Paracentric Cylinder	Silicon bronze/copper alloy
Lock Size	13-3/8" H 9" W x 3-18" D
Latchbolt Throw	1"
Electrical	24 VDC, 1.5 watt continuous duty
Tumblers	Spring Tempered brass. Tumblers actuated by phospher bronze springs, six per lock
Air Requirement	Consumption: 1.1 cubic inches per operation. Supply pressure: 80-100 P.S.I. at the door.

ASTM F 1577 Certified Impact Test-Grade 1



For More information please call 210-533-1231